

Compact size and Enhanced usability

# SLK-CB125



Εκτυπωτής κύβος μικρού μεγέθους

Δομή για εύκολη συντήρηση

Σχεδιασμός για βελτιωμένη χρηστικότητα

Βολική δομή ελέγχου εμπλοκών

Συμπαγές μέγεθος για εύκολη τοποθέτηση στον πάγκο.

Υποστηρίζει ευέλικτη έξοδο εκτύπωσης: μπροστινή έξοδος ή επάνω έξοδος.

Ιδανικός για εκτυπωτή κουζίνας/μπαρ με μελωδικό ήχο (βομβητής κουζίνας)




Wi-Fi



Bluetooth



Γραμμωτός  
κώδικας




Πλάτος  
χαρτιού



Εύκολη  
φόρτωση



Γρήγορη  
ταχύτητα



Συμπαγής  
σχεδιασμός



Εύκολη  
συντήρηση



Τριπλή  
διεπαφή

## ΕΦΑΡΜΟΓΕΣ



## ΧΑΡΑΚΤΗΡΙΣΤΙΚΑ



ΧΑΡΑΚΤΗΡΙΣΤΙΚΑ  
ΕΚΤΥΠΩΤΗ

### Print Method

Direct thermal

### Print Speed

250mm/sec(9.8ips)

### Print Width

80mm (640 Dots/Line)

### Resolution

203 DPI

### Power

Power type : External SMPS

AC : 110~220Vac 50/60Hz

DC : 24Vdc / 2.5A

### Sensor

Paper end, Cover open,

Paper low (Front-Exit Mode  
Only)

### Reliability

TPH life : 150km

**MCBF** : 80 Million lines

Cutter life : 2.0 Million cuts

Cutter method: Partial / Full cut

### Drawer port

2 circuit(24V, Max. 1A)



ΦΥΣΙΚΑ  
ΧΑΡΑΚΤΗΡΙΣΤΙΚΑ

### Dimension (W x D x H)

125×131.5×125mm

(4.92"×5.17"×4.92")

### Weight

0.91kg



ΔΙΕΠΑΦΕΣ

### Standard

1 : USB (B type)+Serial  
(RS- 232C\_9pin)+Ethernet

Built-in

2 : USB (B type)+Serial  
(RS232C-

9Pin)+RJ45(Serial)

### Optional

Bluetooth Smart Ready

(Bluetooth 5.0+BLE) or

WiFi(802.11 a/b/g/n ) B/T,

WF combo



ΠΙΣΤΟΠΟΙΗΣΕΙΣ

KC, CE, FCC, IC, CB, NRTL



ΛΕΙΤΟΥΡΓΙΚΑ  
ΧΑΡΑΚΤΗΡΙΣΤΙΚΑ

**Operating Temperature** 0 ~ 45°C

### Operating Humidity

10 ~ 80%

**Storage Temperature** -10 ~ 60°C

### Storage Humidity

10 ~ 90%



ΧΑΡΑΚΤΗΡΙΣΤΙΚΑ  
ΜΕΣΩΝ ΕΝΗΜΕΡΩΣΗΣ

### Media Type

Thermal receipt paper

### Media Width

58mm / 80mm / 82.5mm

### Media Core Diameter

12.5mm ± 0.5mm

### Media Roll Diameter

Max. ø 83mm

### Thickness

0.06~0.08mm



ΛΟΓΙΣΜΙΚΟ

### Emulations

ESC/POS Command  
compatible

### Drivers

Windows Driver(XP ~,  
Server2003 ~), Linux  
Driver, Mac Driver, OPOS  
Driver, JavaPOS Driver

### SDK

Android SDK, iOS SDK,  
Windows SDK



Γραμματοί Κώδικες

1D

EAN-8, EAN-13, Code 39,  
Code 93, Code 128, ITF,  
UPC-A, UPC-E, Codabar

2D

PDF 417, QR code



ΓΡΑΜΜΑΤΟΣΕΙΡΕΣ / ΓΡΑΦΙΚΑ

### Character Type

FontA (12x24), Font B(9x17),

Chinese(Traditional/Simplified, 24x24),

Korean(24x24), Japanese(24x24)

### Characters per line (CPL)

· 180 DPI

Font A(12x24) : 46/42/30 columns

Font B(9x17) : 62/59/40 columns

· 203 DPI

Font A(12x24) : 53/48/35 columns

Font B(9x17) : 71/64/46 columns

### Character set

Alpha Numeric Character : 95

Expend Graphic : 128x18 Page (1 space  
page) International Character : 16



ΑΞΕΣΟΥΑΡ

### Standard

Power Adaptor 24Vdc / 2.5A

### Optional

Melody Box, 24V Buzzer,  
Paper Guide