

All in One ELO Touch 15E1 - Especificaciones

Model	15E1
Processor	Intel 1.66GHz Atom N270, 512K L2 Cache, 533MHz System Bus
Chipset	Intel 945GSE Express
Video	Intel Graphics Media Accelerator 950
BIOS	Phoenix
Memory (RAM)	1GB DDR2 SODIMM on 1 of 1 slot (Replaceable with 2GB maximum ¹ on 1 slot)
Hard Disk Drive	160GB 2.5" SATA HDD ²

(1) Maximum memory using 1 available slot; replacement for single, pre-installed memory module. Replaceable up to 2GB maximum, SODIMM DDR2-533 (PC2-4200, dual channel) or DDR2-800 (PC2-6400, dual channel).

(2) GB equals one billion bytes when referring to storage capacity. Accessible capacity may be less.


Ports

USB Ports	4 x USB 2.0
Serial Ports	2 x Native DB9 RS-232 (standard)
Ethernet Ports	1 x LAN RJ45 (Gigabit)
Additional Video Out	2nd VGA out
Audio Ports	1x3.5mm line-out

Operating System

Operating Systems Supported	No Operating System <i>Nota: Sistema de hardware compatible con versiones de 32 bits de Microsoft Windows XP, Windows 7, y en general de 32-bit sistemas operativos Linux. Los controladores disponibles para su descarga en las páginas de soporte.</i>
Languages	N/A

Display

Display	15.6" diagonal, active matrix TFT LED LCD
Aspect Ratio	16:9 Widescreen
Useful Screen Area	Horizontal: 13.6" (344mm) Vertical: 7.6" (193mm)
Native (Optimal) Resolution	1366 x 768 at 60 Hz
Colors	262K (6-bit)
Brightness (Typical)	LCD panel: 220 nits iTouch: 198 nits
Response Time—Total (Typical)	16 msec
Viewing Angle (Typical) 	Horizontal: ±40° or 80° total Vertical: 10°/30° or 40° total
Contrast Ratio (Typical)	400:1

Technologies

Touch Technology	iTouch Surface acoustic wave
------------------	--

Power

Power Supply	External 12VDC universal-type power supply brick AC input voltage: 100-240VAC Input frequency: 50-60Hz Maximum output power: 50W (Max draw: 57.5W)
Power Consumption (Max. without peripherals.)	38W

Dimensions

Máximum Touchcomputer Dimensions	Width: 15.4" (390mm) Height: 11.0" (280mm) Depth: 9.5" (240mm)
Touchcomputer Dimensions (With Stand)	Width: 15.4" (390mm) Height: 13.0" (330mm) Depth: 6.3" (161mm)
Shipping Box Dimensions (W x H x D)	18.1" (460mm) x 15.8" (400mm) x 9.8" (250mm)

Weights

Weight	Actual with stand: 9.9 lb (4.5 kg) Shipping: 15.2 lb (6.9 kg)
--------	--

Environmental

Temperature	Operating: 0°C to 35°C (32°F to 95°F) Storage: -30°C to 60°C (-22°F to 140°F)
Humidity (Non-Condensing)	Operating: 20%-80% Storage: 5%-95%

Other

Form Factor	Desktop
Mounting Options	Wall mount or secure base to tabletop/desktop
Enclosure Color	Black
Real-Time Clock	Replaceable lithium-ion battery for clock
MTBF	50,000 hours demonstrated
Sealing	<ul style="list-style-type: none"> • Touchscreen sealed to bezel • Touchscreen sealed to LCD
Other Features	<ul style="list-style-type: none"> • Serviceable internal components • Removable baseplate • Threaded holes on bottom of base for secure mounting • Kensington security lock
Power Cables	North American and European power cable included; other regions available upon request.