

# TOSHIBA

## BV400 Series

### Desktop Printers

---

- The latest print technology incorporated into a sleek case design for ultimate user experience.
- Powerful and scalable system architecture that future-proves your investment.
- A broad set of standard interfaces and optional Wi-Fi or Bluetooth for effortless integration into even the most complex IT environments.
- Optional UHF RFID encoding available for the BV410T printers.



**TOGETHER**  
**INFORMATION**

# The Ever-Changing Workplace

## Delivering reliability to meet future challenges

Every business is unique. That's why Toshiba offers the most reliable print solutions that meet all your labelling requirements, day after day. Toshiba barcode printers provide connectivity and solutions to adapt to the needs of an ever-changing workplace.

Toshiba's barcode printers continue to deliver on our promise of Together Information – our commitment to collaborate with clients to provide tailored, cost-effective solutions that meet your evolving workplace needs.

## A strong combination of excellent design & advanced connectivity

This most advanced desktop printer series consists of nine different models, all with a small footprint, intelligent design which brings simplicity and efficiency for the ultimate user experience. Enhanced connectivity features enable these printers to be integrated into various networks and, thanks to print language emulations, into almost every print scenario. The robustness of the printer series offers high print quality and performance comparable to mid-ranged printers.

# Stylish Design with Outstanding Performance

## Designed with the user in mind

A compact footprint was a core criteria in the design of the BV400 desktop printer range. With its ergonomic style and sleek casing these printers suit retail shops, offices or any type of workplace where space is at a premium.

## A model to meet every need

With models available in 203 dpi and 300 dpi versions, also available in black or white cabinets, the BV400 series suits to fit into almost any operating environment.

- **BV400D direct thermal printers** with a compact and stylish design and an increased throughput of up to 7 ips.
- **BV420D-GL linerless** prints on adhesive labels with no backing paper, reducing waste and keeping the working environment safe and clean.
- **BV400T thermal transfer printers** enables optional RFID encoding and supports a wide range of ribbons from wax to resin.



## Key highlights

- Market leading throughput with up to 7 ips
- Compact & sleek design with a small footprint
- Intuitive & clear user experience
- Vast print languages & emulations
- RFID encoding available with thermal transfer printers
- SOTI Connect certified for IoT device management

# Exceeding Expectations

## Ease of use

The integrated LCD screen of the BV410 models provides clear information and notifications alert the user via the colour change of the status LEDs. Changes can be made to the main settings directly on the printer and full printer setup is also available by remote connection.

## Future-ready operating system

The redesigned OS platform supports multi print emulations, which enable simple integration into complex IT environments. This platform extends the connectivity and adaptability of the BV400 printers to keep pace with the requirements of an ever-changing workplace.

## Speed & efficiency

For printing labels quickly and efficiently the BV400 has market leading print speeds of up to 7 inches per second and an advanced CPU for fast processing of data. With it's rapid boot-time the printer is ready to print from power-on.

## Solid reliability

Designed for the most demanding retail environments the renowned reliability of these desktop printers support busy operations – day after day. The optional built-in AC adapters ensure a tidy and safe workplace.

## IoT device management

Adding support for SOTI Connect to Toshiba desktop printers enables businesses to trace large printer fleets and overcome printer management challenges such as remote access for firmware updates and automated rule deployment.

## RFID encoding

Toshiba's unique RFID technology is now incorporated into the BV410T desktop printer models, opening a wide-range of new applications across multiple markets. With these new options and an extensive range of features, the BV400 series offers solutions that are usually reserved for industrial printers only.

## Linerless printing

The BV420D-GL linerless printer can print on adhesive labels with no backing paper, reducing waste and keeping the working environment safe and clean:

- Toshiba's true label saving technology automatically shortens the length of the label to use only that material that is printed on. This eliminates material waste and saves money.
- With up to 30% more linerless labels per roll you can increase print time, reduce roll changes and lower storage requirements.
- Toshiba linerless labels are completely flexible as they can print to any length of label required without changing the roll.
- Printing on only the length required saves paper and resources and no backing paper means no additional industrial waste.



# Specifications

## General

	BV410D		BV410T		BV420D		BV420T		BV420D-GL
Model	BV410D-GS02	BV410D-TS02	BV410T-GS02	BV410T-TS02	BV420D-GS02	BV420D-TS02	BV420T-GS02	BV420T-TS02	BV420D-GS02
Print method	Direct thermal		Thermal transfer, direct thermal		Direct thermal		Thermal transfer, direct thermal		Direct thermal
Resolution	203 dpi (8 dots/mm)	300 dpi (11.8 dots/mm)	203 dpi (8 dots/mm)	300 dpi (11.8 dots/mm)	203 dpi (8 dots/mm)	300 dpi (11.8 dots/mm)	203 dpi (8 dots/mm)	300 dpi (11.8 dots/mm)	203 dpi (8 dots/mm)
Print head	Flat head				Flat head				Flat head
User interface	2x LED, 3x key with LCD				3x LED, 2x key				3x LED, 2x key
Memory	128 MB (FROM), 128 MB (SRAM)				128 MB (FROM), 128 MB (SRAM)				128 MB (FROM), 128 MB (SRAM)
Operating temperature / humidity	5° to 40°C (41° to 104°F) / 25 to 85% non-condensing relative humidity (RH)				5° to 40°C (41° to 104°F) / 25 to 85% non-condensing relative humidity (RH)				5° to 35°C (41° to 95°F) / 25 to 85% non-condensing relative humidity (RH)
Storage temperature / humidity	-20° to 60°C (-40° to 140°F) / 10 to 90% non-condensing relative humidity (RH)		-40° to 60°C (-40° to 140°F) / 10 to 90% non-condensing relative humidity (RH)		-20° to 60°C (-40° to 140°F) / 10 to 90% non-condensing relative humidity (RH)		-40° to 60°C (-40° to 140°F) / 10 to 90% non-condensing relative humidity (RH)		-20° to 60°C (-40° to 140°F) / 10 to 90% non-condensing relative humidity (RH)
Power supply	AC 100-240 V, 50/60 Hz				AC 100-240 V, 50/60 Hz				AC 100-240 V, 50/60 Hz
Case	white				black				black
Dimensions (W x D x H)	174 x 218 x 173 mm		200 x 267 x 198.3 mm		174 x 218 x 173 mm		200 x 267 x 198.3 mm		174 x 288 x 173 mm
Weight	2.0 kg		2.9 kg		2.0 kg		2.9 kg		2.6 kg

## Print

	BV410D		BV410T		BV420D		BV420T		BV420D-GL
Model	BV410D-GS02	BV410D-TS02	BV410T-GS02	BV410T-TS02	BV420D-GS02	BV420D-TS02	BV420T-GS02	BV420T-TS02	BV420D-GS02
Sensor	Reflective, transmissive				Reflective, transmissive				Reflective
Max. print speed	7 ips (177.8 mm/s)	5 ips (127 mm/s)	7 ips (177.8 mm/s)	5 ips (127 mm/s)	7 ips (177.8 mm/s)	5 ips (127 mm/s)	7 ips (177.8 mm/s)	5 ips (127 mm/s)	7 ips (177.8 mm/s)
Max. print width	108 mm	105.7 mm	108 mm	105.7 mm	108 mm	105.7 mm	108 mm	105.7 mm	99 mm
Print length:									
Batch	8-997 mm		6-997.9 mm		8-997 mm		6-997.9 mm		6-997.9 mm
Cut <sup>1)</sup>	19.4-993 mm		20.4-997.9 mm		19.4-993 mm		20.4-997.9 mm		25.4-152.4 mm
Peel-off <sup>1)</sup>	23.4-150.4 mm		21.4-148.4 mm		23.4-150.4 mm		21.4-148.4 mm		25.4-152.4 mm
Barcodes	UPC/EAN/JAN, Code 39, Code 93, Code 128, EAN 128, NW7, MSI, Interleaved 2 of 5, Industrial 2 of 5, Matrix 2 of 5, POSTNET, RM4SCC, KIX Code, Customer Barcode, GS1 DataBar, USPS Intelligent Mail Barcode								
2D Codes	Data Matrix, PDF 417, MaxiCode, QR Code, Micro PDF 417, Micro QR, GS1 Data Matrix, Aztec Code								
Fonts	Bitmap, Outline, Preisfont, optional TTF, Writable Characters								



# Specifications

Media	BV410D		BV410T		BV420D		BV420T		BV420D-GL
	BV410D-GS02	BV410D-TS02	BV410T-GS02	BV410T-TS02	BV420D-GS02	BV420D-TS02	BV420T-GS02	BV420T-TS02	BV420D-GS02
Modell									
Alignment	Centred				Centred				Centred
Backing paper width	25.4 to 118 mm				25.4 to 118 mm				32-102 mm
Label thickness	0.06 to 0.19 mm		0.06 to 0.19 mm		0.06 to 0.19 mm		0.06 to 0.19 mm		0.06-0.19 mm
Inner media core diameter	25.4/38.1/42/76.2 mm		25.4/38.1/40/42/76.2 mm		25.4/38.1/42/76.2 mm		25.4/38.1/40/42/76.2 mm		38.1 mm
Outer media roll diameter:									
Standard	Max. 127 mm		Max. 127 mm		Max. 127 mm		Max. 127 mm		Max. 107 mm
Optional	Max. 214 mm		Max. 214 mm		Max. 214 mm		Max. 214 mm		-
Media format	Roll, fanfold								Roll

## Software & connectivity

Software & connectivity	BV410D		BV410T		BV420D		BV420T		BV420D-GL
	BV410D-GS02	BV410D-TS02	BV410T-GS02	BV410T-TS02	BV420D-GS02	BV420D-TS02	BV420T-GS02	BV420T-TS02	BV420D-GS02
Modell									
Language mode	TPCL, Basic Command Interpreter (BCI)								
Emulation	ZPL II, DPL, SBPL, IPL								
Printer driver	Windows 11/10/8/7 (32/64 bit), Windows Server 2019/2016/2012 R2/2012, SAP, Linux/Unix, macOS X								
SDK	iOS, Android								
Interface	USB 2.0, Ethernet 10/100 Base T (IPv4 & IPv6), WLAN 802.11a/b/g/n (Dual Band für 2.4 GHz/5 GHz) <sup>1)2)</sup> , Bluetooth V2.1 EDR MFi certified <sup>1)2)3)</sup> , Bluetooth V5.2 EDR MFi certified <sup>1)2)4)</sup> , RS-232-C (serial port) <sup>1)</sup>								
Label software	BarTender UltraLite (included)								
IoT device management	e-FleetManager <sup>1)</sup> , SOTI Connect								

## Options

### For BV400D series

Full cutter module, partial cutter module, peel-off module, RS-232-C serial interface board, WLAN module, Bluetooth module, AC adapter cover, external media stand for max. 214mm Outer media roll diameter (not for GL model)

### For BV400T series

Full cutter module, partial cutter module, peel-off module, RS-232-C serial interface board, WLAN module, Bluetooth module, AC adapter cover, external media stand for max. 214mm Outer media roll diameter (not for GL model)

- 1) Optional  
 2) Availability varies from country to country  
 3) For BV400D series  
 4) For BV400T series



## About Toshiba Tec

Toshiba Tec Germany Imaging Systems GmbH is part of the globally operating Toshiba Tec Corporation, active in various high-tech industrial sectors.

Toshiba Tec Corporation is a leading provider of information technology, operating across multiple industries - ranging from retail, education and business services to hospitality and manufacturing. With headquarters in Japan and over 70 subsidiaries worldwide, Toshiba Tec Corporation helps organisations transform the way they create, record, share, manage and display information.

For more information please contact us:

### **Toshiba Tec Germany Imaging Systems GmbH**

Carl-Schurz-Str. 7  
41460 Neuss  
Germany

### **Telephone**

+49 2131-1245-0

### **Fax**

+49 2131-1245-402

### **Website**

[www.toshibatec.eu](http://www.toshibatec.eu)



**Together Information is Toshiba's vision for how people and organisations create, record, share, manage and display ideas and data.**

**It is based on our belief that the most successful organisations are those that communicate information in the most efficient way.**

**We make that possible through an integrated portfolio of industry-specific solutions, all of which reflect Toshiba's commitment to the future of the planet.**

