

# EPSON TM-U295 Printer



Just 1.6 kg {approx. 3.5 lb} and ultra-compact, the TM-U295 is the world's smallest slip printer. It is also versatile. Select from among four print sizes and four printing directions. Or, use page mode to tell the printer where to print on the page. The TM-U295 is also equipped with a host of user-friendly features, such as an easy-to-operate touch panel and an automatic paper eject function. And, for the widest range of applications, connect the TM-U295 to an EPSON Intelligent Module.

The world's smallest slip printer, perfect for POS terminals.

### World's Smallest Slip Printer

Measuring a mere 180 × 190.5 × 101.5 mm (W × D × H) {7.1 × 7.5 × 4.0"} and weighing in at only 1.6 kg {approx. 3.5 lb}, the TM-U295 is the world's smallest slip printer. The small size and simple design of this printer make it a good match for any business.

### Variety of Printing Formats

With four character sizes and four printing directions, the TM-U295 flexibly adapts to your slip printing needs. Further, you can use page mode to print characters practically anywhere on the slip.

### User-friendly

Features such as an easy-to-use touch panel and automatic paper feedout maximize user-friendliness. In addition, the ASB function, which automatically sends the status of the printer, enables the operator to monitor the printer status.

### NT and IT Series Connectivity

The TM-U295 can be used with EPSON's Intelligent Modules, saving space and offering a broad range of application choices for your business.

### ESC/POS®

The TM-U295 conforms to EPSON's ESC/POS command system. High expandability and easy upgradability ensure efficient use of existing software assets.

### Superb Reliability

EPSON's world-renowned quality and reliability are reflected in every component and mechanism of the TM-U295, ensuring products unsurpassed in performance and dependability.

EPSON **TM-U295** Printer**TM-U295 Specifications**

<b>Print Method</b>	7-pin, shuttle impact dot matrix
<b>Print Font</b>	5 × 7 / 7 × 7
Column capacity	35 / 42 columns
Character size	1.6 × 2.9 mm (W × H) / 1.3 × 2.9 mm (W × H) {0.063 × 0.114" / 0.051 × 0.114"}
Character set	95 Alphanumeric, 32 International, 128 × 3 Graphic
Characters per 25.4 mm	13.5 cpi / 16.2 cpi
<b>Print Speed</b>	2.1 lps
<b>Data Buffer</b>	512 bytes or 35 bytes
<b>Interfaces</b>	RS-232C / Bi-directional parallel
<b>Paper Dimensions</b>	Slip: 80 to 182 × 69 to 257 mm (W × L) {3.15 to 7.17 × 2.72 to 10.12"}
<b>Paper Thickness</b>	0.09 to 0.35 mm {0.0035 to 0.0137"}
<b>Copy Capability</b>	One original and two copies
<b>Inked Ribbon</b>	ERC-27 (purple)
<b>Ribbon Life</b>	1,500,000 characters
<b>Power</b>	24 VDC ± 10%
<b>Current Consumption</b>	Approx. 600 mA (at 24 VDC)
<b>D. K. D. Function</b>	2 drivers
<b>Reliability</b>	MTBF 180,000 hours MCBF 7,000,000 lines
<b>Overall Dimensions</b>	180 × 190.5 × 101.5 mm (W × D × H) {7.1 × 7.5 × 4.0"}
<b>Mass</b>	Approx. 1.6 kg {3.5 lb}
<b>EMI Standards</b>	VCCI class A, FCC class A, CE marking
<b>Safety Standards</b>	UL / CSA C22.2 No. 950

Inch values are approximate.

cpi: characters per 25.4 mm (characters per inch)

lps: lines per second

Specifications are subject to change without notice.