



# Stellar Series

Stellar-S 1.5"



## TECHNICAL DETAILS

Stellar-S		
Product Dimensions (mm*mm*mm)	48*35*13	
Active Display Area (mm*mm)	27*27	
Weight (g)	21.7	
Case Color	Elegant white or customized	
Display Size (inch)	1.5	
Resolution (pixel)	200*200	
DPI	188	
Display color	BWR, BWY	
NFC	<p>"N"means the ESL with NFC function.</p> <ol style="list-style-type: none"><li>1. Complies with ISO/IEC 14443 Type A standard</li><li>2. Supports NFC NDEF data format with 200 bytes writable memory</li><li>3. Communication distance is reachable maximum 10 mm</li><li>4. Batch update of the same template</li></ol>	
Multiple Pages	Supported 4 pages	
LED Flash	Red, Blue, Green	
Working life	3 years (4 updates per day)	
Battery Spec	1*550mAh	
Changeable Battery	Battery Pack	
Working Temperature (°C)	0~30	
Working Humidity (%RH)	30~70	
Protection Level	IP54	
Certification	ROHS,CE,FCC,MIC	
RF Wireless Communicaiton Parameters	Working Frequency: 2402MHz ~ 2480MHz	System Throughput: Up to 18,000 labels per hour