



Stellar Series

Stellar-M 2.1"



TECHNICAL DETAILS

Stellar-M			
Product Dimensions (mm*mm*mm)	70*35*13.2		
Active Display Area (mm*mm)	48.6*23.7		
Weight (g)	36		
Case Color	Elegant white or customized		
Display Size (inch)	2.1		
Resolution (pixel)	250*122		
DPI	131		
Display color	BWR, BWY		
NFC	<p>"N" means the ESL with NFC function.</p> <ol style="list-style-type: none"> 1. Complies with ISO/IEC 14443 Type A standard 2. Supports NFC NDEF data format with 200 bytes writable memory 3. Communication distance is reachable maximum 10 mm 4. Batch update of the same template 		
Multiple Pages	Supported 4 pages		
LED Flash	Red, Blue, Green		
Working life	5 years (4 updates per day)		
Battery Spec	2*550mAh		
Changeable Battery	Battery Pack		
Working Temperature (°C)	0~30		
Working Humidity (%RH)	30~70		
Protection Level	IP54		
Certification	ROHS,CE,FCC,MIC		
RF Wireless Communicaiton Parameters	<table border="1"> <tr> <td>Working Frequency: 2402MHz ~ 2480MHz</td> <td>System Throughput: Up to 18,000 labels per hour</td> </tr> </table>	Working Frequency: 2402MHz ~ 2480MHz	System Throughput: Up to 18,000 labels per hour
Working Frequency: 2402MHz ~ 2480MHz	System Throughput: Up to 18,000 labels per hour		