

# TP-610

Compact & Cost-effective  
Impact Receipt Printer



# TP610

## SPECIFICATIONS



<b>Printing method</b>	24 Dot Matrix
<b>Printing direction</b>	Unidirectional or bidirectional printing
<b>Resolution</b>	180×180 DPI (Max.)
<b>Print speed</b>	Normal speed: 1.5 lines/s (25 columns,10 cpi);6.35 mm/s High speed:2.5 lines/s (25 columns,10 cpi);10.58 mm/s Super high speed:5 lines/s (25 columns,10 cpi) ;21.12 mm/s
<b>Paper feed speed</b>	140 mm/s (Max.)
<b>Copy</b>	Original + 1 copy
<b>Paper type</b>	Roll paper (normal paper, black mark paper, copy paper)
<b>Paper specifications</b>	Paper model Normal single sheet roll paper Normal two-sheet copy paper Paper width 45±0.5 mm, 57.5 ±0.5 mm, 76 ±0.5 mm, 80 ±0.5 mm Thickness Single sheet roll paper: 0.06 ~ 0.085 mm Two-sheet copy paper (each page): 0.05 ~ 0.08 mm, total thickness≤0.14 mm Maximum diameter 100 mm
<b>Printing width</b>	Max. 63.4 mm
<b>Character per line</b>	Paper width 76 ±0.5 mm 57.5 ±0.5 mm 45±0.5 mm ASCII character (10 CPI) 25 CPL 19 CPL 15 CPL
<b>Character set</b>	ASCII character set, International character set
<b>Character size</b>	ASCII: 2.54×2.54 mm
<b>Character dot matrix:</b>	24×24
<b>Character pitchASCII:</b>	10 CPI, 12 CPI, 15 CPI, and proportional pitch
<b>Line spacing 1</b>	1/6 inch, 1/8 inch, programmable in 1/360 inch increments
<b>Bar code</b>	EAN-13, EAN-8, Interleaved 2 of 5, Matrix 2 of 5, Industrial 2 of 5, Code 39, Code 128 B, Code 128 C, NW-7
<b>Two-dimension code</b>	QR code, Chinese-sensible code
<b>Emulation</b>	EPSON ESC/PK2, ESC/POS
<b>Ribbon Model:</b>	JMR137 (support to replace the ribbon core JMR214)
<b>Life:</b>	3 million characters
<b>Interface</b>	This printer can be equipped with the following interfaces: Parallel interface: Centronics USB interface: 2.0 Full-Speed USB interface (2.0 Full-Speed)+ Ethernet interface (10/100Base-T) Bluetooth interface Wi-Fi Bluetooth(802.11b/g/n)
<b>Cash drawer interface</b>	RJ-11, 24V (DC)/1A
<b>Black mark</b>	Standard
<b>Input buffer</b>	256 KB
<b>Environmental</b>	Operating environment Temperature: 5 ~ 35°C 25 ~ 80%RH (No condensation)
<b>Storage Temperature</b>	-40 ~ 55°C Humidity:≤93%RH (40°C, No condensation)
<b>Weight</b>	Approximately 2.7 Kg (With auto-cutter type) Approximately 2.5 Kg (Without auto-cutter type)
<b>Noise</b>	< 54 dB (A) (ISO7779 standard)
<b>Control panel</b>	2 keys and 3 LED indicators
<b>Physical dimensions</b>	163 mm(Width) × 262 mm (Depth) × 145 mm(Height)
<b>Power supply</b>	Voltage: 198 ~ 242 V (AC)
<b>Frequency:</b>	50 ~ 60 Hz