

PD220V-V Customer Display



**Clear, Easy-to-read
Vacuum Fluorescent Display**



- Supports 11 command modes included EPSON etc.
- Power supply from 5V to 24V to prevent any mindless use of improper power input.
- OPOS/JPOS driver is standard.

- 20-column x 2-line dot matrix in a wide viewing angle.
- Easy connectivity to a wide range of POS products.

PD220V-V Customer Display

Specification

Model	PD220V-V
Series	PD Series
Interface	RS232/ USB
Display Method	Vacuum Fluorescent Display (Blue-green)
Number of characters	40 (20 columns* 2 lines)
Brightness	500~1000 cd/m2
Character font	5* 7 dot matrix
Character type	95 Alphanumeric, 32 International Characters
Character size	9.02(H)* 5.25(W)mm
Dot Size (X* Y)	0.86* 1.05mm
Download characters	9 characters
Pole Dimension	Per support length: 339(L)* 34(Dia)mm
Viewing Aangle	Max. 135°
Horizontal Rotation	Max. 355°
Command Mode	LD220,EPSON POS D101, AEDEX, UTC/S, UTC/P, ADM788, DSP800, CD5220, EMAX, LOGIC CONTROL
Language Support	FRENCH, DEUTSCH, ENGLISH, DENISH, SWISS, ITALIAN, SPANISH, JAPANESE, SLAVONIC, RUSSIAN, PORTUGUESE, CANADIAN, CANADIAN, NORDIC, TURKISH, GREEK, WEST EUROPEAN LATIN, CP858, CP860, WPC1252, CP857 (TURKISH), POLISH,WPC1250,WPC1253, (GREEK), WPC1255 (HEBREW) , WPC1251, CP866, CP852, CP737 (GREEK) CP858, CP864 (ARABIC), FARSI (IRAN)
Connection	Baud rate direct connection 9600 or 19,200 bps
Reliability	MTBF 30,000 hours
Consumption	5~24V DC
Panel Dimension	3.15(W)* 19.5(D)* 5.4(H)cm
Base Dimension	12(W)* 14(D)* 2.5(H)cm
Minimum Height	27.5cm
Maximum Height	40cm
Net Weight	0.75kg
Packing Dimension	25*15*10cm
Gross Weight	1kg