



15 inch Projective Capacitive Full-Flat LCD Monitor

Zenis POS 6000

Glossy Piano Finish POS Terminal

- Replaceable Front Bezel
- SAW Touch Version Available
- Clean & Neat Cable Routing Design
- Modularized & Sleek Exterior Design
- Optional Peripherals Designed to Fit with Zenis POS, Giving a Complete POS Solution Experience



POS Systems POS-6000

15 inch Projective Capacitive Full-Flat LCD Monitor



Specifications

Model	POS-6000-i
Main Board	
CPU	Intel® Core™ i5 3320M , 2.6GHz (3M Cache, up to 3.30 GHz)
Chipset	Intel QM77
System Memory	2 x DDR3 SO-DIMM 1333MHz, up to 16GB
Graphic Memory	Share System Memory
OS Support	POS Ready 2009, POS Ready 7, XP Pro, Vista, Linux, Windows 7
Display	
Screen Size	15" (Customer display is optional)
Brightness	300 nits
Resolution	1024 x 768 Pixel
Touch Screen	5 Wire Resistive Type or Projective Capacitive
Tilting Angle	15~80 Degrees (up to 90 degree possible)
Storage	
HDD	1 x 2.5" SATA Bay for HDD or SSD
Compact Flash	1 x CFast Slot for SATA I / SATA II
Interface	
Serial	4 x COM (3 x DB9, 1 x RJ45 with power output, 5/12V selectable)
Parallel	Optional
USB	2 x USB 3.0 (External), 4 x USB 2.0 (External), 3 x USB 2.0 (Internal, reserved for touch screen, Wi-Fi, and MSR)
PS/2 Mouse	
PS/2 Key Board	1 x mixed PS2
LAN	1 x RJ-45, Giga LAN Support
VGA	1 x DB-15, Female
DC Out	1 x 12VDC Jack for Customer Display or 2nd LCD Display (10.4")
Cash Drawer	1 x RJ-11, 12/24 VDC
Audio Jack	1 x Line Out, 1 x MIC In, 1 x Internal Speaker 2W
Others	
Power Input	12VDC 90W, 4-pin Connector with Lock (External Adaptor: 100~240 VAC, 50/60HZ)
Color	Silver, Black, White
Compliance	FCC / CE / WEEE / RoHS
Weight	6.7 Kg
Dimension (W x D x H: mm)	391.2(W) x 245.0(D) x 352.3(H)
Operating Temperature	0°C~40°C
Operating Humidity	20%~80% RH non-condensing