










COMPARISON OF SIGNOTEC SIGNATURE PADS

The following list is intended exclusively to serve as a research tool and makes no claims to being accurate, correct, complete or current. Any liability is therefore excluded!

	Sigma LITE	Sigma	Omega	Zeta	Gamma	Delta Signature Pad	Delta Pen-Display	Kronos Pen-Display	Epsilon Pen-Display
Image									
Display type	No display	Monochrome LCD	Full-colour TFT LCD	Monochrome LCD	Full-colour LCD	Full-colour LCD	Full-colour LCD	Full-colour LCD	Full-colour LCD
Display size	✘	4" (10.4 cm)	5" (12.8 cm)	4.5" (11.4 cm)	5" (12.6 cm)	10.1" (25.6 cm)	10.1" (25.6 cm)	11.6" (29.5 cm)	15.6" (39.5 cm)
Backlight	✘	with or without backlight	✓	with or without backlight	✓	✓	✓	✓	✓
Colour	✘	✘	✓	✘	✓	✓	✓	✓	✓
Surface technology	Robust Polycarbonate surface coating.	Robust signing surface with ITO conductive coating and exclusive dual-layer membrane.	Robust signing surface with ITO conductive coating and exclusive dual-layer membrane.	Hardened glass with native scratch resistance. It is up to three times more scratch resistant than other glass compositions.	Hardened glass with native scratch resistance. It is up to three times more scratch resistant than other glass compositions.	Hardened glass with native scratch resistance. It is up to three times more scratch resistant than other glass compositions.	Hardened glass with native scratch resistance. It is up to three times more scratch resistant than other glass compositions.	Hardened glass with native scratch resistance. It is up to three times more scratch resistant than other glass compositions.	Hardened glass with native scratch resistance. It is up to three times more scratch resistant than other glass compositions.
Expected lifetime	2 million signatures	1 million signatures	1 million signatures	30 million signatures	30 million signatures	30 million signatures	30 million signatures	30 million signatures	30 million signatures
Number of colours	n/a	16 brightness levels b/w	65,536 (High Color)	16 brightness levels b/w	16,7 Mio. (True Color)	16,7 Mio. (True Color)	16,7 Mio. (True Color)	16,7 Mio. (True Color)	16,7 Mio. (True Color)
LCD resolution	n/a	320 x 160 pixels	640 x 480 pixels	320 x 200 pixels	800 x 480 pixels	1.280 x 800 pixels	1.280 x 800 pixels	1.920 x 1080 pixels	1.920 x 1080 pixels
Scrolling	✘	✓	✓	✘	✓	✓	✓	✓	✓
Authentication capability	✓	✓	✓	✓	✓	✓	Monitor Extension	Monitor Extension	Monitor Extension
Unlimited softkeys	✓	✓	✓	✓	✓	✓	Monitor Extension	Monitor Extension	Monitor Extension
Design									
Manufacturing	Germany	Germany	Germany	Germany	Germany	Germany	Germany	Germany	Germany
Software development/support									
SENSOR									
Sensor technology	Resistive Touch Panel (RTP)	Resistive Touch Panel (RTP)	Resistive Touch Panel (RTP)	Electromagnetic Resonance Technology (ERT); Suitable for on-screen hand writing. Sensitive to ERT Stylus only, no influence by hand touch, no erroneous input.	Electromagnetic Resonance Technology (ERT); Suitable for on-screen hand writing. Sensitive to ERT Stylus only, no influence by hand touch, no erroneous input.	Electromagnetic Resonance Technology (ERT); Suitable for on-screen hand writing. Sensitive to ERT Stylus only, no influence by hand touch, no erroneous input.	Electromagnetic Resonance Technology (ERT); Suitable for on-screen hand writing. Sensitive to ERT Stylus only, no influence by hand touch, no erroneous input.	Electromagnetic Resonance Technology (ERT); Suitable for on-screen hand writing. Sensitive to ERT Stylus only, no influence by hand touch, no erroneous input.	Electromagnetic Resonance Technology (ERT); Suitable for on-screen hand writing. Sensitive to ERT Stylus only, no influence by hand touch, no erroneous input.
Active signing area	91 x 45 mm	91 x 45 mm	100 x 75 mm	96 x 60 mm	108 x 65 mm	217 x 136 mm	217 x 136 mm	356 x 144 mm	344 x 194 mm
Pressure sensor unit	1.024	1.024	1.024	1.024	1.024	2.048	2.048	2.048	2.048
Pen type	Tethered passiv stylus with changeable cartridge	Tethered passiv stylus with changeable cartridge	Tethered passiv stylus with changeable cartridge	Tethered active stylus with changeable tip	Tethered active stylus with changeable tip	Tethered active stylus with changeable tip	Tethered active stylus with changeable tip	Tethered active stylus with changeable tip	Tethered active stylus with changeable tip
Battery free pen	✓	✓	✓	✓	✓	✓	✓	✓	✓
Internal sampling rate	6.000 pps	6.000 pps	6.000 pps	-	-	-	-	-	-
Coordinate accuracy	+/- 1.5 % in x, y and z	+/- 1.5 % in x, y and z	+/- 1.5 % in x, y and z	+/- 0.4 mm (center)	+/- 0.4 mm (center)	+/- 0.4 mm (center)	+/- 0.4 mm (center)	+/- 1.0 mm (center)	+/- 0.5 mm (center)
Sensor resolution	2.214 x 1.130 ppi	2.214 x 1.130 ppi	1.387 x 1.040 ppi	2.487 x 2.499 ppi	2.400 x 2.910 ppi	1.264 x 1.292 ppi	1.264 x 1.292 ppi	5.223 x 5.136 ppi	5.084 x 5.067 ppi
Detectable height	-	-	-	5 - 15 mm	5 - 15 mm	5 - 15 mm	5 - 15 mm	5 - 15 mm	5 - 15 mm
Signature sampling report rate	500 pps	500 pps	500 pps	500 pps	500 pps	500 pps	500 pps	280 pps	250 pps
ELECTRONICS / DIGITISATION									
Communication/connectivity	Secure HID-USB; High-Speed WinUSB	Secure HID-USB; High-Speed WinUSB; Optional hardware FTDI VCOM	Secure HID-USB; High-Speed WinUSB; Optional hardware FTDI VCOM	Secure HID-USB; High-Speed WinUSB; Optional hardware FTDI VCOM	Secure HID-USB; High-Speed WinUSB; Optional hardware FTDI VCOM	Secure HID-USB; High-Speed WinUSB; Ethernet (optional Power over Ethernet)	Secure HID and DisplayLink*-Technology	Secure HID and DisplayLink*-Technology	Secure HID and DisplayLink*-Technology
HID-USB (64KB/sec)	✓	✓	✓	✓	✓	✓	✓	✓	✓
USB Full Speed (12 MB/sec)	✘	✘	✓	✓	✓	✓	✓	✓	✓
USB High Speed (460 MB/sec)	✘	✘	✓	✓	✓	✓	✓	✓	✓
RS232 via USB (virtual com port)	✓	✓	✓	✓	✓	✓	✘	✘	✘
RS232 VCOM and USB	RS232 or USB	RS232 or USB	Interchangeable in service-menu	RS232 or USB	Interchangeable in service-menu	Interchangeable in service-menu	✘	✘	✘
Near Field Communication (NFC)	✘	✘	Yes, optional	✘	✘	✘	✘	✘	✘
Advanced Security: Biometric encryption inside the pad	✓	✓	✓	✓	✓	✓	✘	✘	✘
Advanced Security: LCD content signing	✓	✓	✓	✓	✓	✓	✘	✘	✘
Advanced Security: PDF-Signing inside the pad	✓	✓	✓	✓	✓	✓	✘	✘	✘
Create unique cert inside pad	✓	✓	✓	✓	✓	✓	✘	✘	✘
Store customer specific Cert inside pad	✓	✓	✓	✓	✓	✓	✘	✘	✘
Store customer public key inside pad	✓	✓	✓	✓	✓	✓	✘	✘	✘
Internal unique serial number	✓	✓	✓	✓	✓	✓	✓	✓	✓
Status display	2 colored and freely programmable LEDs	2 colored and freely programmable LEDs	2 colored and freely programmable LEDs	2 colored and freely programmable LEDs	2 colored and freely programmable LEDs	2 colored and freely programmable LEDs	Status LED	Status LED	Status LED
Software	Several SDKs available for integration.	Several SDKs available for integration.	Several SDKs available for integration.	Several SDKs available for integration.	Several SDKs available for integration.	Several SDKs available for integration.	Tablet-PC API, SDK for pen input, mouse input	Tablet-PC API, SDK for pen input, mouse input	Tablet-PC API, SDK for pen input, mouse input
Memory	✘	✓	Internal memory for 10 pictures which can be used for static content (fast switching between different pages) and slide shows.	✓	Internal memory for 10 pictures which can be used for static content (fast switching between different pages) and slide shows.	Internal memory for 32 pictures which can be used for static content (fast switching between different pages) and slide shows.	✘	✘	✘
Real signature device or monitor extension	Real signature device	Real signature device	Real signature device	Real signature device	Real signature device	Real signature device	DisplayLink Monitor Extension	DisplayLink Monitor Extension	DisplayLink Monitor Extension
Power supply	USB	USB	USB	USB	USB	USB Y-cable	USB Y-Cable	External Power adapter (AC 100-240 V; 50/60 Hz)	USB, external Power adapter (AC 100-240 V; 50/60 Hz)
OPERATING AND STORAGE CONDITIONS									
Surface liquid resistance	✓	✓	✓	✓	✓	✓	✓	✓	✓
Operational temperatures	-10°C to +60°C	-10°C to +60°C	-10°C to +45°C	-10°C to +45°C	-10°C to +45°C	-10°C to +45°C	-10°C to +45°C	-10°C to +45°C	-10°C to +45°C
Storage temperature	-25°C to 70°C	-25°C to 70°C	-25°C to 70°C	-25°C to 70°C	-25°C to 70°C	-25°C to 70°C	-25°C to 70°C	-25°C to 70°C	-25°C to 70°C
Humidity	<= 90% non-condensing	<= 90% non-condensing	<= 90% non-condensing	<= 90% non-condensing	<= 90% non-condensing	<= 90% non-condensing	<= 90% non-condensing	<= 90% non-condensing	<= 90% non-condensing
MISCELLANEOUS									
Operating systems	Windows 7 (or newer), Windows Server 2012 (or newer), 32- and 64-Bit, Terminal Server (RDP, Citrix), Linux	Windows 7 (or newer), Windows Server 2012 (or newer), 32- and 64-Bit, Terminal Server (RDP, Citrix), Linux	Windows 7 (or newer), Windows Server 2012 (or newer), 32- and 64-Bit, Terminal Server (RDP, Citrix), Linux	Windows 7 (or newer), Windows Server 2012 (or newer), 32- and 64-Bit, Terminal Server (RDP, Citrix), Linux	Windows 7 (or newer), Windows Server 2012 (or newer), 32- and 64-Bit, Terminal Server (RDP, Citrix), Linux	Windows 7 (or newer), Windows Server 2012 (or newer), 32- and 64-Bit, Terminal Server (RDP, Citrix), Linux	Windows 7 (or newer), Windows Server 2012 (or newer), 32- and 64-Bit	Windows 7 (or newer), Windows Server 2012 (or newer), 32- and 64-Bit	Windows 7 (or newer), Windows Server 2012 (or newer), 32- and 64-Bit
Development environments	Desktop and Web SDK/API: .Net Assembly (C#, VB), C++, Java, ActiveX, Linux, browser integration (JavaScript/WebSocket)	Desktop and Web SDK/API: .Net Assembly (C#, VB), C++, Java, ActiveX, Linux, browser integration (JavaScript/WebSocket)	Desktop and Web SDK/API: .Net Assembly (C#, VB), C++, Java, ActiveX, Linux, browser integration (JavaScript/WebSocket)	Desktop and Web SDK/API: .Net Assembly (C#, VB), C++, Java, ActiveX, Linux, browser integration (JavaScript/WebSocket)	Desktop and Web SDK/API: .Net Assembly (C#, VB), C++, Java, ActiveX, Linux, browser integration (JavaScript/WebSocket)	Desktop and Web SDK/API: .Net Assembly (C#, VB), C++, Java, ActiveX, Linux, browser integration (JavaScript/WebSocket)	Monitor Extension	Monitor Extension	Monitor Extension
Browser support	Chrome, Opera, Firefox, MS IE, MS Edge	Chrome, Opera, Firefox, MS IE, MS Edge	Chrome, Opera, Firefox, MS IE, MS Edge	Chrome, Opera, Firefox, MS IE, MS Edge	Chrome, Opera, Firefox, MS IE, MS Edge	Chrome, Opera, Firefox, MS IE, MS Edge	Monitor Extension	Monitor Extension	Monitor Extension
Customization	Yes, min. 50 units	Yes, min. 50 units	Yes, min. 50 units	Yes, min. 50 units	Yes, min. 50 units	Yes, min. 50 units	Yes, min. 50 units	Yes, min. 50 units	Yes, min. 50 units
Security/encryption	AES-256 encrypted connection with RSA-key-exchange. Secure mode which doesn't decrypt signature data at host for real-time display.	AES-256 encrypted connection with RSA-key-exchange. Secure mode which doesn't decrypt signature data at host for real-time display.	AES-256 encrypted connection with RSA-key-exchange. Secure mode which doesn't decrypt signature data at host for real-time display.	AES-256 encrypted connection with RSA-key-exchange. Secure mode which doesn't decrypt signature data at host for real-time display.	AES-256 encrypted connection with RSA-key-exchange. Secure mode which doesn't decrypt signature data at host for real-time display.	AES-256 encrypted connection with RSA-key-exchange. Secure mode which doesn't decrypt signature data at host for real-time display.	AES-256 encrypted connection.	AES-256 encrypted connection.	AES-256 encrypted connection.
Terminal server	✓	✓	✓	✓	✓	✓	✓	✓	✓
Data interface	USB	USB	USB	USB	USB	USB and Ethernet (optional)	USB	3-in-1 HDMI	VGA, HDMI, USB
Data cable length	2 or 5 meter fixed cable	2 or 5 meter fixed cable	2 or 5 meter fixed cable	2,7 meter detachable	2,7 meter detachable	2,7 meter detachable	2,7 meter detachable	2,7 meter detachable	2,7 meter (including HDMI, USB and Power adapter)
Input voltage	5 V powered from USB	5 V powered from USB	5 V powered from USB	5 V powered from USB	5 V powered from USB	5 V powered from USB, optional Power over Ethernet	5 V powered from USB	5 V powered from USB	5 V powered from USB
RoHS directive compliant	✓	✓	✓	✓	✓	✓	✓	✓	✓
Touchscreen protectors	-	Optional	Optional	-	-	-	-	-	-
Warranty	2 years (opt. up to 5 years)	2 years (opt. up to 5 years)	2 years (opt. up to 5 years)	2 years (opt. up to 5 years)	2 years (opt. up to 5 years)	2 years (opt. up to 5 years)	2 years (opt. up to 5 years)	2 years (opt. up to 5 years)	2 years (opt. up to 5 years)
TOOLS									
signoIntegrator/2	Included	Included	Included	Included	Included	Included	Included	Included	Included
signoImager/2									
MS-Office Add-In									
Free updates/maintenance for tools and SDK	✓	✓	✓	✓	✓	✓	✓	✓	✓
DIMENSIONS									
Product dimensions (H x D x W)	10 x 160 x 120 mm	10 x 160 x 120 mm	15 x 180 x 191 mm	12 x 177 x 145 mm	12 x 177 x 145 mm	13-23 x 205 x 280 mm	13-23 x 205 x 280 mm	20 x 185 x 299 mm	40 x 248 x 380 mm
Weight	ca 170 gr.	ca 230 gr.	ca 320 gr.	ca 240 gr.	ca 280 gr.	ca 830 gr.	ca 850 gr.	ca 850 gr.	ca 2,5 kg