

Fast, powerful POS printing

Fast retail top-exit



LED operation panel

The three colour LED indicates the printer's status, types of errors and messages.

Tool-free maintenance

Paper jam? No problem for the CT-S601. One hand grip and the cutter is released automatically. No tool is needed. Even if the long-life cutter ever needs to be exchanged. Thanks to it's Snap-In design this only takes 30 seconds.

Internal power supply

All 80mm POS printers from Citizen offer an internal power supply.

CT-S601II

POS, Receipt printer (thermal 3 inch / 80mm)

Applications

- Hospitality
- Journal
- Kitchen
- Retail



More features for reliable printing

Specifications

CT-S601II

POS, Receipt printer (thermal 3 inch / 80mm)

Features & Benefits

- Paper exit: Top exit - ideal for all retail applications
- Paper load: Easy paper loading
- Printing Speed: Fast print out of receipts - up to 200mm per seconds
- Low space requirement - integrated power supply enables clean work station
- Mobile-POS ready
- Easy notification - built-in buzzer
- ENERGY STAR® compliant
- Small footprint
- Recyclable packacking
- Tool-free maintenance



Top of the class

CITIZEN

CT-S601II

POS, Receipt printer (thermal 3 inch / 80mm)

Model	CT-S601II
Printing Technology	Direct Thermal
Resolution	203 dpi
Print Speed (maximum)	220 mm /sec.
Print Width (maximum)	45 / 48 / 52 / 54 / 64 / 68 / 72 / 80 mm
Media Width (min to max)	58 / 60 / 80 / 83 mm (+/- 1mm)
Media Thickness (min to max)	65 to 75 µm or 75 to 85 µm
Main Interface	None: interface card slot for optional card
Optional interfaces	Premium Wireless LAN, Bluetooth with Apple™ MFi compatibility, Compact Wireless LAN, Serial (RS-232C compliant), Parallel (IEEE 1284 compliant), USB, USB with hub, Powered USB, Ethernet + USB host
Power supply	100 – 240V, 50-60 Hz, external power supply (supplied) or 24V DC
Reliability	200 Million pulses or 150 Km, 2 million cuts
Control panel	Feed button, 3 LEDs
Emulations (Languages)	ESC/POS™
Drivers and software	Free-of-charge from website, including support for various platforms
Size (W x D x H) and Weight	145x192x148 mm, 2 Kg, DC version 145x192x120, 1.6 Kg
Cutter	Guillotine type, full and partial
EMC and safety standards	CE, UL, TUV, C-UL, FCC class A

CITIZEN

All product names are trademarks of the respective manufacturers. Zebra®, ZPL and EPL are trademarks of ZIH Corp. Datamax® is a trademark of Datamax-O'Neil Corporation. Designs, specifications and availability are subject to change without notice. Errors and omissions excluded. © Citizen Systems Europe GmbH, V.1.0

CT-S601II

POS, Receipt printer (thermal 3 inch / 80mm)