




Mart



Medical care



Coffee Shop



Features

- Print head over-heat protection, making print head more durable
- Intelligent cutter to avoid paper jam
- All-in-one mainboard design to improve stability
- Low energy consumption, more economic
- Autocutter for convenient printing



D200N/D260N

Direct thermal Printer

Specifications

MODEL	D200N	D260N
Printing method	Direct thermal	
Printing speed	200mm/s	260mm/s
Paper width	79.5 ± 0.5mm	
Printable area	72mm	
Maximum paper diameter	Φ80 mm	
Paper thickness	0.06-0.08mm	
Column capacity	576 dots/line 512 dots/line	
Line space	3.75mm(Changeable by commands)	
Commands	Compatible with ESC/POS	
Interface type	USB / Lan / USB+Serial / USB+Lan / USB+Bluetooth / USB+Wifi	USB+Lan+WiFi USB+Lan+Bluetooth USB+Serial+Lan USB+Serial+Lan+Wifi USB+Serial+Lan+Bluetooth
Character size	ANK, Font A: 12×24 dots Font B: 9×17 dots simplified/traditional Chinese: 24x24 dots	
Dimension	184×140×135mm (D×W×H)	
Gross weight	1.0 kg	
Bar code	UPC-A/UPC-E/JA(EAN13)/JAN8(EAN8)/CODE39/ITF/CODABAR/CODE93/CODE128	
Code page	PC347(Standard Europe), Katakana, PC850(Multilingual) , PC860(Portuguese), PC863(Canadian-French), PC865(Nordic), WestEuropeGreek, Hebrew, East Europe, Iran, WPC1252, PC866(Cyrillic#2), PC852(Latin2), Pc858, IranII, Latvian, Arabic, PT151(1251)	
2D Code	///	QR CODE / PDF417
Cutter	Partial	
Cutter life	1.5 million cuts	
Print head life	150KM	
Input buffer	64 Kbytes	128 Kbytes
NV Flash	256 Kbytes	
Power adaptor	AC110V/220V, 50~60Hz	
Power source	DC 24V/2.5A	
Input voltage	DC 24V/2.5A	
Cash drawer output	DC 24V/1A	
Work environment	Temperature: 0~45°C , humidity: 10~80RH%	
Storage environment	Temperature: -10~60°C , humidity: 10~90RH%	
Operating system	Windows / Linux	



www.ics.gr

