

ADVANCED DOT IMPACT PRINTER

LK-D30

- Drop-in paper loading
- 5 Lines/sec high speed printing
- Two color printing
- Auto cutter(Optional)
- Paper end / Cover open / Paper low sensor
- Black mark sensor(Optional)



● APPLICATION



● SPECIFICATION

| | | | | | | | |
|-------------------|--|---|--------------------|----------------------|----------------------------------|---|---------------|
| PRINTING | METHOD | 9-pin Serial Dot Impact Matrix | RELIABILITY | PRINT HEAD | 18million lines | | |
| | DIRECTION | Bi-directional(with logical seeking) | | MCBF | 120million characters | | |
| | SPEED | 5 lines/sec | | AUTO CUTTER | 1,000,000cuts(guillotine) | | |
| | RESOLUTION | 160DPI / 80DPI | | | INTERFACE | Serial, Parallel, USB, Ethernet, Wi-Fi(802.11b), Combo(USB+Serial) | |
| | NO. OF COLUMNS | TM-U200 Emulation : 42/35, 40/33 Other Emulation : 40/33 | | EMULATION | | TM-U200, TM-U300, iDP-3540, SP200 Command Compatible | |
| | | NO. OF TOTAL DOTS | | | 400 dots/line | | DRIVER |
| | FONT SIZE | 7x9, 9x9 / 5x9, 7x9 | | POWER | TYPE | External SMPS | |
| | LINE SPACING | n/144inch | | | AC | 100 - 240Vac 50/60Hz | |
| PRINTING WIDTH | 63.5mm | | DC | 24Vdc / 2.5A | | | |
| PAPER | TYPE | Roll paper | | TEMPERATURE | OPERATION | 5 - 40°C | |
| | WIDTH | 57.5mm, 69.5mm, 76.2mm | | | STORAGE | -20 - 60°C | |
| | DIAMETER | MAX. 80mm | | DIMENSION | 156mm x 243mm x 150mm(W x D x H) | | |
| | COPIES | Original + 2copies | | | WEIGHT | 2.38kg(Cutter included) | |
| INK RIBBON | FDC 29 Compatible(Black, Purple, Black/Purple) | | COLOR | Cool Gray, Tri-color | | | |