

## Touch POS System



VESA Mount Capable



Compact 11.6"  
Space-saving



IP54 Whole Unit



## SPECIFICATIONS

### x3S i5

PROCESSOR	Intel Core i3-7020U 2.30GHz FANLESS
SYSTEM MEMORY	1 X SLOT 4GB DDR4 SO DIMM up to 32GB
STORAGE DISK	1 X SLOT 128GB M2

## DISPLAY

SIZE / RESOLUTION	15.6" LED-backlit TFT LCD Resistive Touch)
BRIGHTNESS	300 cd/m2.
TOUCH SCREEN PANEL	Projected capacitive touch (multi-touch)

## I/O INTERFACE

USB PORT	5 x USB 2.0, 1 x USB 3.0 (side)
SERIAL PORT	2 x RJ48 (RS232)
AUDIO PORT	2 x 2 W speakers
CASH DRAWER	1 x RJ11 (24 V)
ETHERNET PORT	1 x RJ45 10/100/1000 Mbps

## OPERATING SYSTEM

WINDOWS	10 IoT (64-bit) / 10 Pro (64-bit) 11 IoT (64-bit) / 11 Pro (64-bit)
LINUX	Kernel 3.0 up

## ENVIRONMENT & MECHANICAL SPECIFICATIONS

DIMENSIONS & WEIGHT	230 (W) x 38-426 (H) x 367 (D) mm   5 kg
CHASSIS MATERIAL	Aluminium die-cast & Polycarbonate-ABS
IP RATING	IP54 whole unit
TEMPERATURE	Operating: 0°C to 40°C   Storage: -20°C to 60°C
HUMIDITY	10% to 90% (non-condensing)
POWER CONSUMPTION	19 V / 3.15 A, external power adaptor, 100-240 V, 50/60 Hz 19 V / 6.31 A, external power adaptor, 100-240 V, 50/60 Hz (printer integrated)

## MODEL OPTIONS

INTEGRATED READERS	3-track MSR, Fingerprint reader, RFID, 2D barcode reader
CUSTOMER DISPLAY	11.6" (1980 x 1080) LCD or 2-line VFD
WIRELESS LAN	Integrated Dual Band Wi-Fi 802.11 b/g/n/ac (2x2 MIMO) + Bluetooth 4.1
COLOURS	Dark Grey (standard)   White (optional)

ALL PRODUCT SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.