Smart Mobile Terminal

SUNMI V3 MIX

MIX, the all-in-one enterprise tablet.



MIX your POS terminal to capture businesses anywhere, anytime.

10"high-resolution display and a built-in high speed printer make a mobile and desktop terminal.

MIX, design not only for payment.

Ergonomically designed for a comfortable grip. Professional scan ner integrated 1D/2D barcode scanning. Aluminum-magnesium alloy fr ame and incell touchscreen make it strong yet slim and light. *All Pictures shown are for illustration purpose only. actual p_roduct may vary

MIX for higher performance.

Qualcomm hexa-core processor and 4GB RAM+32GB ROM for an assured strong performance.

MIX for wider extensibility.



Specially designed rotatable functional cradle enable cash drawer, handheld scanner and network among other accessories that boost your business. <u>*Both rotatable crad</u>le and non-rotatable cradle options are available.

Built-in high speed thermal printer



Professional scanner integrated 1D/2D barcode scanning supported.



NFC reader





SUNMI V3 MIX Application Scenario



SUNMI V3 MIX Tech Specs

General Configuration

Product Model T5701 58mm version T5711 80mm version

Battery Removable Lithium battery 7.2V/2600mAh

Bluetooth BT2.1/3.0/4.2. supports BLE

SIM Card Slot Dual Nano SIM Card slot, Support 1.8V/3.0V

Weight <u>670g(5</u>8mm)/710g(80mm) Camera Front 2MP FF QR Payment 0.3MP FF

(based on Android 13)

OS

SUNMI OS 4.0

Button Power Key, Volume Key and Scan Key

SD Card Slot MicroSD *1

Cradle (Optional) For charging, 3*USB Type A, RJ11, RJ45 **Processor** Qualcomm hexa-core 2.4/2.0GHz

Scanner 2D professional scanner

GPS GPS, AGPS

Fingerprint Only for login (Optional)

Cradle Customer Display (Optional) USB 6.7" touchscreen Memory 4GB RAM+32GB ROM

Wi-Fi Supports IEEE 802.11 a/b /g/n/ac 2.4G/5G

NFC Reader Type A&B card Mifare card, FeLica card ISO/IEC 14443 and ISO 15693 compliant

Power Adapter Input: AC100-240V, Output: 5V/2A

80mm version

Display 10.1" HD 1280*800 IPS

Speaker 1.2W

PSAM Card Slot PSAM Card slot, complies with ISO7816 standard, 1.8V/3.0V

Dimensions (L*W*H) 246*231*73mm

Environment Operating temperature: 0°C-45°C (except 3D camera) Storage temperature: -20°C-60°C

58mm version

Printer

Thermal Printer, Print speed: 70mm/s Paper Roll Width / Diameter: 58mm/ 40mm Thermal Printer, Print speed: 70mm/s

Paper Roll Width / Diameter: 80mm/ 40mm