

# XP-V320N/V330N

## Thermal Receipt Printer

- Wireless port available.
- Wall mount capable.
- Cutter life upgrade to 1.5 million.
- Support cutter auto calibration function.
- Support firmware update online



Coffee Shop



Shopping




Mart



# XP-V320N/V330N

## Thermal Receipt Printer



MODEL	XP-V320N	XP-V330N
Printing method	Direct thermal	
Printing speed	200mm/s	260mm/s
Paper width	79.5±0.5mm	
Printable area	72mm / 52mm	
Maximum paper diameter	Φ80 mm	
Paper thickness	0.06-0.08mm	
Column capacity	576 dots/line(adjustable by commands)	
Line space	3.75mm(Changeable by commands)	
Commands	Compatible with ESC/POS	
Interface type	USB+Serial / USB+LAN	USB+Serial+Lan
Character size	ANK, Font A: 12×24 dots Font B: 9×17 dots simplified/traditional Chinese: 24x24 dots	
Dimension	184×140×142mm ( D×W×H)	
Gross weight	1.0 kg	
Bar code	UPC-A/UPC-E/JAN(EAN13)/JAN8(EAN8)/CODE39/ITF/CODABAR/CODE93/CODE128	
Code page	PC347(Standard Europe), Katakana, PC850(Multilingual) , PC860(Portuguese), PC863(Canadian-French), PC865(Nordic), WestEuropeGreek, Hebrew, East Europe, Iran, WPC1252, PC866(Cyrillic#2), PC852(Latin2), Pc858, IranII, Latvian, Arabic, PT151(1251)	
Cutter	Partial	
Cutter life	1.5 million cuts	
Print head life	100KM	
Input buffer	64 Kbytes	2048 Kbytes
NV Flash	256 Kbytes	
Power adaptor	AC110V/220V, 50~60Hz	
Power source	DC 24V/2.5A	
Input voltage	DC 24V/2.5A	
Cash drawer output	DC 24V/1A	
Work environment	Temperature: 0~45°C, humidity: 10~80RH%	
Storage environment	Temperature: -10~60°C , humidity: 10~90RH%	
Operating system	Win XP/Win Vista/Win 7/Win 8/Win 8.1/ Win10 /Linux	

